

G100 TA

DIRECT FIRED GAS HEATER

Duty (kW/btu)

67.6 - 102.9 kW (230,000 - 351,000 btu)

Air Flow (m³/h/cfm)

180 m³/h (1059 cfm)

Heated Area Typical

2,486 m³ (87,755 ft³)

Power Supply volt/amps

230v 1ph 50hz .47A

Noise Level dba Av.

75 dba @ 1 mtr

Weight

28.2 kg 62 lb

Dimensions w/l/h

470 x 935 x 532 mm

18.5 x 37 x 21 ins

Control

Automatic External Controls Available

Fuel Type

LPG Propane Only

Fuel Consumption

4.79 kg/hr 7.27 kg/hr

Minimum Cylinder(s)

3 x 47 kg

Max. Operating Pressure

2 bar

G260 TA

DIRECT FIRED GAS HEATER

Duty (kW/btu)

25.6 - 77.5 kW (87,350 - 264,000 btu)

Air Flow (m³/h/cfm)

2037 m³/h (1200 cfm)

Heated Area Typical

1,840 m³ (64,952 ft³)

Power Supply volt/amps

230v 1ph 50hz .8A

Noise Level dba Av.

74.5 dba @ 1 mtr

Weight

29 kg 64 lb

Dimensions w/l/h

490 x 940 x 535 mm

19.25 x 37 x 21 ins

Control

Automatic External Controls Available

Fuel Type

LPG Propane Only

Fuel Consumption

1.8 kg/hr 5.5 kg/hr

Minimum Cylinder(s)

3 x 47 kg

Max. Operating Pressure

1 bar

