

## G30 TA

### DIRECT FIRED GAS HEATER

**Duty (kW/btu)**

15 - 38.6 kW (51,180 - 131,707 btu)

**Air Flow (m<sup>3</sup>/h/cfm)**

750 m<sup>3</sup>/h (441.38 cfm)

**Heated Area Typical**

923 m<sup>3</sup> (32,581 ft<sup>3</sup>)

**Power Supply volt/amps**

230v 1ph 50hz Run .39A

**Noise Level dba Av.**

72 dba

**Weight**

15.5 kg 34 lb

**Dimensions w/l/h**

372 x 610 x 480 mm

14.6 x 24 x 19 ins

**Control**

Automatic External Controls Available

**Fuel Type**

LPG Propane Only

**Fuel Consumption**

1.15 kg/hr 2.84 kg/hr

**Minimum Cylinder(s)**

2 x 47 kg

**Max. Operating Pressure**

1.5 bar

## G125 TA

### DIRECT FIRED GAS HEATER

**Duty (kW/btu)**

8.8 - 36.6 kW (30,025 - 124,000 btu)

**Air Flow (m<sup>3</sup>/h/cfm)**

680 m<sup>3</sup>/h (400 cfm)

**Heated Area Typical**

875 m<sup>3</sup> (31,250 ft<sup>3</sup>)

**Power Supply volt/amps**

230v 1ph 50hz Run .41A

**Noise Level dba Av.**

67.2 dba @ 1 mtr

**Weight**

18 kg 39.7 lb

**Dimensions w/l/h**

380 x 630 x 425 mm

15 x 25 x 16.7 ins

**Control**

Automatic External Controls Available

**Fuel Type**

LPG Propane Only

**Fuel Consumption**

.8 kg/hr 2.1 kg/hr

**Minimum Cylinder(s)**

2 x 47 kg

**Max. Operating Pressure**

1 bar

